

36 Septic Tanks & Cesspools



Please contact us for pricing and availability when enquiring as these may be subject to a lead time.

GRP Septic Tanks



- Three Chamber System to collect and hold sewage.
- Inlet & Outlets to collect wastewater.
- Tested to BSEN12566:1 and CE-marked to ensure compliance with latest environmental and Building Regulations requirements.
- Traditional 'onion-style' tanks for standard installations.
- Pedestrian Cover & Frames Included as standard.
- Horizontal Tanks also available for larger size requirements, these are available up to 20000 Litres.

Size	Diameter	Height	Inlet invert	Inlet dia	Outlet invert	Outlet dia
2800L	1870	2780	1000	110	1040	110
3800L	2075	3000	1000	110	1040	110
4500L	2196	3100	1000	110	1040	110

Cesspools



- Watertight Covered Tanks used for storing sewage.
- No outlet & No Treatment is involved.
- High Level Alarms Recommended to indicate when nearly full.
- Available with up to 20000 Litres storage holding.
- 500mm Invert on all CessPools.
- 50 Year Design Life & 25 Year Warranty included

Model	Length	Width	Height	Inlet invert	Inlet dia
AT2800	3000	1250	1750	500	110
AT3800	4000	1250	1750	500	110
AT4500	2650	1600	2100	500	110

Excellent levels of stock, outstanding service



Specialist Supplier of Plastic Drainage & Ducting Products

Tel: 01428 300200
sales@rupipe.co.uk



Widely Regarded as one of the most efficient, reliable and economical treatment plants, Ensign Treatment Plants are available at Rupipe ranging from 4-140pe.



Marsh Ensign Standard/Ultra Treatment Plant

- Tested & Approved to BSEN12566-3/A1:2009 standard
- Complete with Compressor, Alarm & Impermeable Heavy Duty Lid
- With a range of 4 to 140pe plants available as standard - Larger Sizes are available on request
- Shallow Dig Option available on request

Model (pop)	Length	Width +/-100mm	Height	Inlet invert	Inlet dia	Outlet invert	Outlet dia
6	2860	1912	1600	500	110	575	110
8	2860	1912	1600	500	110	575	110
10	2860	1912	1600	500	110	575	110
12	2860	1912	1600	500	110	575	110



Kingspan Biodisc Treatment Plant

- Certified to BSEN12566-3
- Rotating Biological Contactor Technology,
- Suitable for 4-18 people
- Supplied with a control panel & alarm



Kingspan Bioficient Treatment Plant

- Certified to BSEN12566-3
- Shallow dig plant
- Suitable for home with up to 30 people
- Supplied with a control panel & alarm

Competitive pricing, reliability you can trust



Specialist Supplier of Plastic Drainage & Ducting Products

Tel: 01428 300200
www.rupipe.co.uk

38 Pumping Stations & Interceptors




Our Pump stations are designed to BSEN12050 for structural strength and water-tightness and to BSEN752 to comply with hydrostatic and electrical requirements.




- The smooth internal walls and integral pump well improves pump efficiency.
- Unique 'keying-in' lip to assist anchoring into concrete surround.
- Variable invert depths and orientations - to suit individual site conditions.
- Pre-assembled pipework for fully automatic operation.
- Heavy duty (industrial) 'peardrop' floats and market leading pumps throughout ensure robust, reliable design and maximum efficiency.

Fuel & Oil Interceptors



- Designed and tested to BS EN858 parts 1&2
- Used to separate fuel & oil from surface water, preventing polluting the water that drains away.
- Our range includes full retention separators, forecourt separators & bypass separators.



Flow Control Units



- Chamber, inlet & outlet dimensions are varied to give a wide variety of flow control units with differing characteristics.
- Flow Control Units are self activating, there are no moving parts meaning there is no power supply required. They are manufactured in robust stainless steel construction.
- These are customized and built to order in a variety of sizes. Please contact us for any enquiry you may have.

Excellent levels of stock, outstanding service



Tel: 01428 300200
sales@rupipe.co.uk